

IPS100 Specifications



Key Features

- Indoor applications
- Modules are 32x16 matrices
- Multiple communications options
- Made of only the highest quality LEDs
- Manufactured in the United States
- Direct Drive

Specifications

Physical	Pixel Pitch	10.32mm (.400") centers
	Pixel Configuration	1 red, 1 green, 1 blue
	Pixel Density	9,688 m ² / 900 ft ²
	Diode Density	29,064 m ² / 2,700 ft ²
	Module Configuration	32x16 pixels
	Diode Type	Surface Mount Device (SMD)
	Module Dimensions (LxH)	330x165 mm / 12.99"x 6.50"
	Module Weight	0.27kg / .60 lbs
	Cabinet Construction	All aluminum construction

Electrical	Video Rate	60 frames per second
	Animation Rate	60 frames per second
	Video Processing	24 bit, 100% digital, no compression
	Color Processing	16 bit per color (48 bit total)
	Input Power Range	120/240 volts, 50/60 Hz
	Refresh rate	49,920hz
	Scan Rate	1:1 (Non-multiplexed)
	Calibration	Pixel to pixel - Module to module
	Calibration White Point	D65 - 6500K
	Calibration Standards	REC 709, REC 2020 or Max Gamut

Optical	Brightness	2,000 nit
	Contrast Ratio	8,000:1
	Viewing angle - Horizontal	160° (+/- 80°)
	Viewing angle - Vertical	160° (+/- 80°)
	Number of colors	281 trillion colors
	Gray Scale Intensity	65,536 levels of red, green, and blue
	Dimming Capability	256 levels of brightness
	Color temperature - Default	6,500K
Color temperature - Adjustable	4,500 - 9,000K	

Operational	Working Temperature	-32°C to 55°C / -30°F to 131°F
	Cooling	Quiet running vent fans
	Weather Proofing	IP56
	LED Lifetime (1/2 brightness)	100,000 hours
	Certification	CE, UL / ULC listed
	Service	Front Service and/or Rear Service

 **Prismview**
A Samsung Electronics Company